# **Tubular Industrial Process**

## **Screw Plug Immersion Heaters**



# Standard (Non-Stock) and Stock Screw Plug Immersion Heaters

Stock Items Are Shown In RED


#### 60 watts/in² (9.3 watts/cm²) — Typical Applications: Deionized Water • Demineralized Water

- \* 316 Stainless Steel Screw Plug
- \* 316 SS Sheath Heating Elements
- \* NEMA 1 Terminal Housing

**NOTE:** Part Numbers followed by a ① are 3-Phase only. Other 3-Phase heaters are convertible to 1-Phase.

Nominal	Immersed Length				Approximate Net Weight			
Pipe Size	in	mm	KW	120V-1Ph	240V-3Ph	480V-3Ph	lbs	kgs
	75%	194	3	TSP01822	TSP01823	TSP01824①	7	3
	10%	270	4.5	TSP01825	TSP01826	TSP01827①	7	3
	14%	372	6	_	TSP01828	TSP01829	8	4
2-1/2" NPT	17%	448	7.5	_	TSP01830	TSP01831	8	4
3 elements	20%	524	9	_	TSP01832	TSP01833	9	4
	261/8	664	12	_	TSP01834	TSP01835	10	5
	31%	803	15	_	TSP01836	TSP01837	11	5 )
	371/8	943	18	_	TSP01838	TSP01839	12	5

**Screw Plug** Heater **Dimensions** 



S	Screw Plug	Minimum Hole Diameter		"A" "B"		,"	"(	"C" Thermowell Bulb Size		Standard Cold Ends (CE)		Element Diameter			
	NPT	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm
	1"	1-1/8	29	7/8	22	1-1/4	32	1-3/8	35	1/4	6.4	1	25	.315	8
	1-1/4"	1-3/8	35	15/16	24	1-5/16	33	1-3/4	44	1/4	6.4	1	25	.315	9
	2"	2-1/4	57	1-1/16	27	1-9/16	40	2-1/2	64	3/8	9.5	2	50	.430	11
	2-1/2"	2-1/2	64	1-5/16	33	2-1/16	52	3	76	3/8	9.5	2	50	.475	12

#### **Ordering Information**

#### **Catalog Heaters**

Screw Plug Immersion Heaters whose Part Numbers are in **RED** are in stock for immediate delivery.

Standard Non-Stock Part Numbers are stocked as sub-assemblies for 2-3 week delivery.

#### Custom Engineered/Manufactured Heaters

Understanding that an electric heater can be very application specific, for sizes and ratings not listed, **TEMPCO** will design and manufacture a Screw Plug Immersion Heater to meet your requirements.

Standard lead time is 4 weeks.

## **Please Specify** the following:

- ☐ Wattage, Voltage and Phase
- ☐ Screw Plug Size and Material ☐ Element Sheath Material
- ☐ Element Watt Density
- ☐ Element Immersion Length
- ☐ Electrical Enclosure Type
- ☐ Thermostat— if required
- Optional Features

**WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.